

JLG® **CONSTRUCTION LIFT** **EXTEND-A-REACH**



40H+6 ■ 60H+6
80HX+6 ■ 100HX+10

**NEW ARTICULATING BOOM EXTENSION
FOR GETTING WORK DONE OVER, UNDER
AND BEHIND OBSTACLES.**

60H+6

60H/60H+6 COMPARISON CHART		
SPECIFICATIONS	JLG 60H	JLG 60H+6
MAXIMUM HEIGHT	60 ft., 0 in.	66 ft., 0 in.
MAXIMUM REACH	49 ft., 10 in.	56 ft., 4 in.
BELOW GROUND	8 ft., 8 in.	14 ft., 7 in.
STOWED LENGTH	25 ft., 11 in.	28 ft., 6 in.
BOOM ANGLES ABOVE HORIZONTAL BELOW HORIZONTAL	75° -21°	75°, +15° ART. -21°, -80° ART.
PLATFORM CAPACITY UNRESTRICTED RESTRICTED	500 lbs. 1,000 lbs.	500 lbs.
PLATFORM SIZES OPTIONAL	36 in. x 60 in. 36 in. x 48 in. 36 in. x 72 in. 36 in. x 96 in.	36 in. x 60 in. 36 in. x 48 in. 36 in. x 72 in.
APPROXIMATE WEIGHT	23,000 lbs.	26,250 lbs.

REACH DIAGRAM

